



Input

**Model Name** Switched PDU  
**Model Number** ATP-1623K-24N1

## Description

230V, 16A, 24 Outlets, Remote Current Monitoring, Remote Power Switch

<b>Current Meter</b>	Digital True RMS Current Meter
<b>Power Monitor</b>	Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
<b>Protocols</b>	Http, Https, SNMP, DHCP, UDP
<b>Outlet Control</b>	Individual Outlet Control
<b>Power Delay</b>	Power On/Off Sequence can be Defined
<b>Alarm Thresholds</b>	User-Defined Alarm Thresholds for Warning and Overload
<b>Event Alert</b>	Email, Trap, Audible Alarm



## Specification

Output	(21) IEC320 C13 (3) IEC320 C19
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker

## Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 24 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP



## Operation

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1778 x 44 mm
Weight	5.3 kg

## Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3  
C-Tick AS/NZS CISPR 22: 2006  
FCC Part 15 Class A, ICES-003

